



T408BC, Titan Brake Parts Cleaner



Section 1: Chemical Product and Company Identification

Manufacturer or Supplier Name: Shrader Canada Limited
Address: 830 Progress Court, Oakville, Ontario L6L 6K1
Date of MSDS Preparation: 02/20/2002 **Revision:** 1
Product Use: Cleaner.
Chemical Family: Petroleum distillates.

Section 2: Composition/Information on Ingredients

Hazardous Ingredients	%	LD50 and LC50	ACGIH TWA	Ecotoxicity - Aquatic Toxicity
HEPTANE 142-82-5	60-100	Inhalation LC50 Rat : 103 gm/m ³ /4H	500 ppm STEL 400 ppm TWA 500 ppm STEL 400 ppm TWA	LC50 (24 hr) goldfish: 4.0 mg/L.; LC50 (24 hr) mosquito fish: 4900 mg/L.; LC50 (96 hr) cichlid fish: 375.0 mg/L.
ISOPROPRANOL 67-63-0	7-13	Inhalation LC50 Rat : 16000 ppm/8H Oral LD50 Rat : 5045 mg/kg Oral LD50 Mouse : 3600 mg/kg Dermal LD50 Rabbit : 12800 mg/kg	(500ppm) STEL (400 ppm) TWA 500 ppm STEL 400 ppm TWA	LC50 (96 hr) fathead minnow (29 days old): 94900-10400 mg/L. Cond: Flow-through, 24.4-24.6 degrees C, pH 7.09, 52.5 mg/L CaCO ₃ .; LC50 (96 hr) fathead minnow (31 days old): 61200-65500 mg/L. Cond: Flow
Carbon Dioxide 124-38-9	1-5	Not Available	30,000 ppm STEL 5000 ppm TWA 30,000 ppm STEL 5000 ppm TWA	Not Available

Section 3: Hazards Identification

Ingestion: Ingestion of small amounts during normal handling are not likely to cause injury. Larger amounts may cause effects similar to those described under inhalation. Ingestion of large amounts may cause stomach irritation. Symptoms include nausea, vomiting and diarrhea. Aspiration into the lungs

during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

- Skin Contact:** No hazard under normal conditions of use. Frequent or prolonged contact may dry and irritate the skin and cause a rash.
- Inhalation:** No hazard under normal conditions of use. High concentrations may cause respiratory irritation and central nervous system depression with results ranging from dizziness and headache to unconsciousness.
- Eye Contact:** Direct contact causes eye irritation.
- Chronic Effects:** Reports have associated repeated and prolonged occupational overexposure to various organic solvents with internal organ, brain and nervous system damage.

Section 4: First Aid Measures

- Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
- Skin Contact:** Wash with soap and water. Remove contaminated clothing and launder before reuse. Seek medical attention if irritation persists.
- Inhalation:** Not a hazard under normal use conditions. If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.
- Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.
- Additional Information:** If symptoms such as convulsions or unconsciousness occur before vomiting, gastric lavage should be considered. Hemodialysis should be considered in severe acute intoxications.

Section 5: Fire Fighting Measures

- | | |
|---------------------------------------|----------------------------------|
| Flash Point (°C): | -14 °C (Liquid Component) |
| Flame Projection: | > 45 cm. Aerosol will flashback. |
| NFPA Classification: | Aerosol, Level 3 |
| Autoignition Temperature (°C): | Not Available |
| Lower Explosive Limit: | Not Available |
| Upper Explosive Limit: | Not Available |

Conditions of Flammability:

Extremely flammable. Do not use on vehicles unless cool. Sprayed product will project a flame on contact with an ignition source. Contents under pressure. Containers may explode is heated. Vapours are heavier than air and may travel or be moved along the ground to an ignition source at locations distant from material handling.

Sensitivity to Mechanical Impact:

Contents under pressure. Protect against physical damage.

Sensitivity to Static Discharge:

Take precautionary measures against static discharges.

Extinguishing Media:

Alcohol foam or water fog for large fires. Carbon dioxide or dry chemical for small fires. Use water spray to cool fire exposed containers and prevent bursting. Do not use a direct stream of water.

Hazardous Combustion:

Carbon dioxide, carbon monoxide and other unidentified organic compounds.

Section 6: Accidental Release Measures

Leak or Spill Procedures:

Contain spilled material. Avoid contamination of natural waterways. Wear suitable protective clothing. Follow applicable explosion and fire precautions during the response. Stop the spill at the source when safe to do so. For large spills, dike the area to prevent spreading. Pump excess to a salvage container. Absorb residues and small spills with a non-flammable absorbent material and collect adsorbate for disposal. For large quantities refer to the environmental ministry.

Section 7: Handling and Storage

Handling Procedures:

Flammable. Keep away from heat, spark, flame and other sources of ignition. Do not use on hot vehicles. Use with adequate ventilation. Avoid breathing vapours. Avoid skin and eye contact. Wear all appropriate personal protective equipment during use. Use good personal hygiene. Avoid smoking, eating and drinking during use. Wash with soap and water after handling. Containers of this material may contain hazardous residues when emptied.

Storage Requirements:

Store in a cool, dry, well-ventilated area. Storage temperatures should not exceed 40°C. Keep from freezing. Keep away from children.

Section 8: Exposure Controls/Personal Protection

Respiratory:	Not normally required. If the TLV is exceeded, a NIOSH-approved respirator is advised.
Gloves:	Nitrile gloves. Neoprene.
Eyewear:	Safety glasses. Contact lenses should not be worn. They may contribute to the severity of the injury.
Clothing:	Sufficient clothing to prevent skin contact.
Ventilation:	Sufficient mechanical ventilation to maintain exposures below the TLV. General mechanical ventilation is not recommended as the sole means of controlling exposure. Make-up air should always be supplied to balance air exhausted.
Other protective equipment	Emergency showers and eyewash facilities should be nearby. The selection of personal protective equipment will vary depending on the conditions of use.

Section 9: Physical and Chemical Properties

Physical State:	Aerosol
Odour:	Characteristic odour.
Appearance:	Colourless.
Evaporation Rate:	Not Available
Vapour Pressure (mmHg):	Not available.
Vapour Density (Air=1):	> 1

VOC %: 100
Boiling Point: Not Available
pH: Not available.
Coefficient of water: Not Available
Solubility in Water: Negligible
Specific Gravity (H2O=1): 0.74 at 15°C
Viscosity: Not available.

Section 10: Stability and Reactivity

Conditions of Instability:

Stable at ambient and moderately elevated temperatures and pressures.

Hazardous Polymerization:

Hazardous polymerization will not occur.

Hazardous Decomposition:

See hazardous combustion products.

Incompatible Materials:

Avoid strong oxidizers such as HOOH, HNO₃, and oleum.

Conditions of Reactivity:

Avoid excessive heat, sparks and open flame.

Section 11: Toxicological Information

Irritancy of Product:

May be mildly irritating to eyes and skin.

Sensitization to product:

Contains no known skin or respiratory sensitizers.

Carcinogenicity:

No components are listed as carcinogens by ACGIH, IARC, OSHA, or NTP.

Reproductive Effects:

Not Available

Teratogenicity:

Not Available

Mutagenicity:

Not Available

Synergistic Products:

Not Available

Other Information:

Exposure limit: ACGIH STEL, (Heptane): 500ppm / 2050mg/m³. Exposure Limist, ACGIH STEL, (Isopropyl Alcohol): 500ppm / 1230mg/m³

Section 12: Ecological Information

Environmental: Toxic to aquatic life. Aromatic hydrocarbons may be bioaccumulative but they have no food chain concentration potential. See composition/information on ingredients.

Biodegradability: Not available.

Section 13: Disposal Considerations

Waste Disposal: Contents under pressure. Do not puncture, incinerate or expose to heat even when empty. Reuse or recycling should be given priority over disposal under any circumstances. Do not dump unused contents into sewers, on the ground or into any body of water. Dispose of in accordance with municipal, provincial and federal regulations.

Section 14: Transportation Information

Road shipment: AEROSOLS, Class 2.1, UN1950, ERG #126.

Marine shipment: AEROSOLS, Class 2, UN1950, EmS# F-E, S-U.
Flash Point (°C): -14 °C (Liquid Component)

Air Shipment: Aerosols, Flammable, Class 2.1, UN 1950, PI Y203.

Exemption: LTD QTY exemptions may be used if product is packaged in accordance with Schedule 1 of TDGR (Clear Language)

Section 15: Regulatory Information

WHMIS: A, B5, D2B

CEPA: All components are listed on the Domestic Substances List (DSL).

CPR Compliance: This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

Section 16: Other Information

HMIS Rating: 241B

Prepared By: Michael Jou, B.A.Sc., Shrader Canada Limited

Information Tel #: 1-905-847-0222, 1-800-201-9486

Information Fax #: (905) 847-5404

CANUTEC EMERGENCY (613) 996-6666
